
STATIONARY DUMPERS

1,000/2,000/4,000/6,000 LBS





CAPACITY

• 1,000/2,000/4,000/6,000 lbs.

BASE SIZES

• 48" wide x 36" long and 50" wide x 50" long

DUMPING ANGLE

• 0° - 120°

RETAINING BAR

- Fixed bar mounted 3" above container height, located above opening
- Spring loaded bar available for multiple container heights (optional)

SAFETY

- Velocity fuse is standard on each cylinder to eliminate dumpers from collapsing due to hose failure
- Hold down tabs in each corner
- Flow control and pressure equalizing valve built in each pump
- Fully enclosed sides to give the dumper stability, avoid spillage and funnel product

POWER SUPPLIES

A/C 110/1/60 volt (standard)
Hand held (standard)

Foot control (optional)

A/C 220-460-575/3/60 volt Hand or foot controlled (optional)

Air/Hydraulic

Foot control (standard) Hand control (optional)

OPTIONS

- Larger/smaller platform sizes
- Increase/reduce pump height
- Portability
- Limit switchcases
- Special electrical controls
- Chute attachments
- Galvanized, stainless steel, "Steel It' epoxy paint
- Stands for higher dumping applications
- Side guards

STATIONARY DUMPER

MODEL NO.	CAPACITY	PLAT. SIZES	DUMP	TILT	R'TEG BAR	OVERALL DIM.
	(LBS.)	(w x d) (IN.)	HEIGHT (E)	ANGLE	(C) (IN.)	(F x B) (IN.)
DUMP HEIGHT 36"						
SD 36-10	1,000	48 x 36	36	0 - 120°	UP TO 40	54 x 52
		50 x 50	36	0 - 120°	UP TO 40	56 x 66
SD 36-20	2,000	48 x 36	36	0 - 120°	UP TO 40	54 x 52
		50 x 50	36	0 - 120°	UP TO 40	56 x 66
SD 36-40	4,000	48 x 36	36	0 - 120°	UP TO 40	54 x 52
		50 x 50	36	0 - 120°	UP TO 40	56 x 66
SD 36-60	6,000	48 x 36	36	0 - 120°	UP TO 40	54 x 52
		50 x 50	36	0 - 120°	UP TO 40	56 x 66
DUMP HEIGHT 48"						
SD 48-10	1,000	48 x 36	48	0 - 120°	UP TO 48	54 x 52
		50 x 50	48	0 - 120°	UP TO 48	56 x 66
SD 48-20	2,000	48 x 36	48	0 - 120°	UP TO 48	54 x 52
		50 x 50	48	0 - 120°	UP TO 48	56 x 66
SD 48-40	4,000	48 x 36	48	0 - 120°	UP TO 48	54 x 52
		50 x 50	48	0 - 120°	UP TO 48	56 x 66
SD 48-60	6,000	48 x 36	48	0 - 120°	UP TO 48	54 x 52
		50 x 50	48	0 - 120°	UP TO 48	56 x 66
DUMP HEIGHT 60"						
SD 60-10	1,000	48 x 36	60	0 - 120°	UP TO 60	54 x 52
		50 x 50	60	0 - 120°	UP TO 60	56 x 66
SD 60-20	2,000	48 x 36	60	0 - 120°	UP TO 60	54 x 52
		50 x 50	60	0 - 120°	UP TO 60	56 x 66
SD 60-40	4,000	48 x 36	60	0 - 120°	UP TO 60	54 x 52
		50 x 50	60	0 - 120°	UP TO 60	56 x 66
SD 60-60	6,000	48 x 36	60	0 - 120°	UP TO 60	54 x 52
		50 x 50	60	0 - 120°	UP TO 60	56 x 66

See page 29 for options available.

STATIONARY DUMPERS

1,000/2,000/4,000/6,000 LBS






PORTABLE DUMPER W/ ADJUSTABLE RETAINING BAR



PORTABLE DUMPER W/ NARROW DISCHARGE CHUTE



WITH LOCK OUT



STATIONARY DUMPER WITH ADJUSTABLE CHUTE ATTACHMENT AND SAFETY SKIRTING



STATIONARY DUMPER W/ADJUSTABLE



W/STAINLESS DISCHARGE CHUTE

& SPECIAL RETAINING SCREEN

SIDE LOADING DUMPER





WHEELED CART DUMPER



OVERARM DUMPER





STATIONARY FORK OVERARM DUMPER FOR DUMPING PORTABLE CONTAINERS



PORTABLE STAINLESS STEEL "V" MAG DUMPER



GALVANIZED DUMPER WITH STAINLESS CHUTE



"STEEL-IT" PAINTED FOOD GRADE DUMPER



STAINLESS STEEL DUMPER



Stainless Glass Bead Finish



PORTABLE CONVEYOR DUMPER WITH CHUTE



STATIONARY DUMPER WITH HYDRAULIC GATES

